

NAME

<code>archive_write_add_filter_b64encode,</code>	<code>archive_write_add_filter_bzip2,</code>
<code>archive_write_add_filter_compress,</code>	<code>archive_write_add_filter_gzip,</code>
<code>archive_write_add_filter_lz4,</code>	<code>archive_write_add_filter_lzip,</code>
<code>archive_write_add_filter_lzma,</code>	<code>archive_write_add_filter_lzop,</code>
<code>archive_write_add_filter_none,</code>	<code>archive_write_add_filter_program,</code>
<code>archive_write_add_filter_uencode,</code>	<code>archive_write_add_filter_xz</code>

LIBRARY

Streaming Archive Library (libarchive, -larchive)

SYNOPSIS

```
#include <archive.h>

int
archive_write_add_filter_b64encode(struct archive *);

int
archive_write_add_filter_bzip2(struct archive *);

int
archive_write_add_filter_compress(struct archive *);

int
archive_write_add_filter_gzip(struct archive *);

int
archive_write_add_filter_lz4(struct archive *);

int
archive_write_add_filter_lzip(struct archive *);

int
archive_write_add_filter_lzma(struct archive *);

int
archive_write_add_filter_lzop(struct archive *);

int
archive_write_add_filter_none(struct archive *);

int
archive_write_add_filter_program(struct archive *, const char * cmd);

int
archive_write_add_filter_uencode(struct archive *);

int
archive_write_add_filter_xz(struct archive *);
```

DESCRIPTION

<code>archive_write_add_filter_b64encode(),</code>	<code>archive_write_add_filter_bzip2(),</code>
<code>archive_write_add_filter_compress(),</code>	<code>archive_write_add_filter_gzip(),</code>
<code>archive_write_add_filter_lz4(),</code>	<code>archive_write_add_filter_lzip(),</code>
<code>archive_write_add_filter_lzma(),</code>	<code>archive_write_add_filter_lzop(),</code>
<code>archive_write_add_filter_uencode(),</code>	<code>archive_write_add_filter_xz(),</code>

The resulting archive will be compressed as specified. Note that the compressed output is always properly blocked.

archive_write_add_filter_none()

This is never necessary. It is provided only for backwards compatibility.

archive_write_add_filter_program()

The archive will be fed into the specified compression program. The output of that program is blocked and written to the client write callbacks.

RETURN VALUES

These functions return **ARCHIVE_OK** on success, or **ARCHIVE_FATAL**.

ERRORS

Detailed error codes and textual descriptions are available from the **archive_errno()** and **archive_error_string()** functions.

SEE ALSO

tar(1), libarchive(3), archive_write(3), archive_write_format(3),
archive_write_set_options(3), cpio(5),mtree(5), tar(5)